PRODUCT DATA SHEET
TERRAXX

Product Code: DMS025

Delta Terraxx is a dimpled sheet with a geotextile layer which acts as a surface layer.

Terraxx has been optimised for various applications in horizontal drainage. Laid on top of the waterproofing, this 2-ply water drainage sheet constitutes an all-round solution conforming to DIN 18531 and DIN 4095. It serves to protect e.g. paved underground parking decks, terraces, and planted roofs from impounded water and is installed under the wearing course of parking decks.

info@deltamembranes.com

www.deltamembranes.com

01992 523 523

© 2019 Delta Membrane Systems Ltd All Rights Reserved

PRODUCT DATA SHEET
TERRAXX

Product Code: DMS025

BENEFITS

•Reliably Protects and insulates waterproofing layers against mechanical damage
• Withstands extreme compression loads of 400 kN/m2
• High drainage capacity prevents frost damage and encrustations
• Water-vapour pressure is drained away through the structure
• Water drainage capacity exceeds that of gravel or chipping layers
• Easy and cost-efficient installation

SPECIFICATION

• NBS Specification J40 295A flexible sheet tanking/damp proofing

ASSOCIATED PRODUCTS

• Delta Terraxx-Schraube
• Delta Terraxx Profile
• Delta MS Dubel
• Koster Waterproofing
• Delta Adhesive Pins

Head Office:
Delta House, Merlin Way, North Weald, Epping, Essex, CM16 6HR
01992 523 523 | info@deltamembranes.com | www.deltamembranes.com

PRODUCT DATA SHEET
TERRAXX

Product Code: DMS025

TECHNICAL DATA

Stud Height	9mm (approx)
Roll Size	2.4m x 12.5m
Material	High Density Polyethylene
Compressive Strength	400 kN/m2 (approx)
Temperature Resistance	-30˚C to +80˚C



Head Office:
Delta House, Merlin Way, North Weald, Epping, Essex, CM16 6HR
01992 523 523 | info@deltamembranes.com | www.deltamembranes.com